



EASYSHIFT 75W90

PRODUCT DESCRIPTION

KENNOL EASYSHIFT 75W90 is a fully synthetic extreme pressure oil developed for mechanical gearboxes and heavy loads exposed axles. KENNOL EASYSHIFT 75W90 is especially formulated to answer the T.D.L. (Total Drive Line) concept. Meeting the most severe standards regarding transmission, KENNOL EASYSHIFT 75W90 is recommended for gearboxes with noise or synchronization problems.

PROPERTIES

KENNOL EASYSHIFT 75W90 is formulated from synthetic bases and top level performance additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear additives	Material life extended
Excellent thermal and gear stability	Optimal performance over time
High extreme pressure level	Ideal for use in final reductions (axles)
High viscosity at high temperature	High operational safety
Low viscosity at low temperature	Easier gear shift when cold

SPECIFICATIONS

KENNOL EASYSHIFT 75W90 has been developed to meet the highest international standards, including :

SAE	75W90
API	GL4 / GL5 / MT1
MIL.L.	PRF-2105E
SCANIA	STO 1:0
MAN	341 type E3/Z3, 342 type S1, 3343 type S
VOLVO	97307 / 97312
MB	235.8
Viscosity @ 40°C, cSt	77
Viscosity @ 100°C, cSt	15,2
Viscosity Index	209
Density @ 20°C	0,867
Pour Point (°C)	< -40
Flash Point (°C)	> 210

KENNOL EASYSHIFT 75W90 has been developed to answer the needs of your mechanical tranquility, since unusual noises or hazardous synchronization are not just a comfort issue. We call that "optimal performance" and that's why this product was born on the track.

Direct download here : http://www.kennol.com/FT/EASYSHIFT_75W90.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.