

ENERGY + 5W30

PRODUCT DESCRIPTION

KENNOL ENERGY PLUS 5W30 is a fully synthetic motor oil mainly intended for gasoline engines of recent US and Asian vehicles, turbo-compressed or not, with direct or indirect injection. KENNOL ENERGY PLUS 5W30 has been developed to protect downsized motors from the low speed pre-ignition phenomenon (LSPI).

Compatible for vehicles using LPG, biodiesel and bioethanol (up to 85% - E85).

PROPERTIES

KENNOL ENERGY PLUS 5W30 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
High fluidity	Allows fuel saving and helps to protect environment
Low volatility	Allows low oil consumption
High dispersing power	Enables your engine to be better cleaned and reduces exhaust fumes
High thermal stability	Guarantees good protection at high temperature

SPECIFICATIONS

KENNOL ENERGY PLUS 5W30 has been developed to meet the highest international standards, including :

SAE	5W30
API	SN / SN Plus / SP
CHRYSLER	MS 6395
FORD	946-A
GM	DEXOS 1 : 2015
ILSAC	GF5 / GF6-A
Viscosity @ 40°C (cSt)	65
Viscosity @ 100°C (cSt)	11
Viscosity Index	170
Viscosity CCS (cP)	4200 (@ -30°C)
Density @ 20°C	0,85
Viscosity HTHS (@ 150 °C under high shear 10 ⁶ s-1) (cP)	3,1
Pour Point, °C	-37
Flash Point, °C	> 210
TBN (mg KOH/g)	8,5

KENNOL ENERGY PLUS 5W30 has been mainly developed to answer the needs of modern engines and vehicles. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_ENERGY_PLUS_5W30_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2020 KENNOL. All rights reserved.