

KART RACING 2T

PRODUCT DESCRIPTION

KENNOL KART RACING 2T is a top level fully synthetic oil developed for 2-stroke engine kartings (100 or 125 cm³, with or without gearboxes) running in competition or under extreme conditions.

KENNOL KART RACING 2T is compatible with unleaded petrol.

The blending lubricant-fuel must meet the manufacturer recommendations but generally the dosage is situated between 2 and 8% of lubricants in the fuel.

PROPERTIES

KENNOL KART RACING 2T is formulated from synthetic bases and “new generation” additives providing excellent properties :

FEATURES	BENEFITS
Very high detergent and antiwear properties	Prevents clogging up and wear of pistons even under extreme conditions
High lubricating power	Optimal operational safety even under extreme conditions
New generation additives	Compatibility with unleaded petrol
Selected synthetic bases	Fumes and clogging reduced in the exhaust systems

SPECIFICATIONS

KENNOL KART RACING 2T has been developed to meet the highest international standards, including :

API	TC
JASO	FD
ISO	L-EGD
Viscosity @ 40°C (cSt)	65
Viscosity @ 100°C (cSt)	10,2
Viscosity Index	145
Density @ 20°C	0,882
Flash Point, °C	>110

KENNOL KART RACING 2T has been mainly developed to answer the needs of demanding kart applications. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_KART_RACING_2T_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2013 KENNOL. All rights reserved.