

## LDS FLUID

### PRODUCT DESCRIPTION

KENNOL LDS FLUID is a fully synthetic fluid especially adapted for central hydraulics "Hydractive 3" (Electro-Hydraulic power assisted steering systems, suspensions,...) for vehicles from the PSA group (Peugeot, Citroën) as well as some Rolls-Royce vehicles.

Do not use where the manufacturer recommends mineral fluid of LHM type.

### PROPERTIES

KENNOL LDS FLUID is formulated from high quality bases and performance additives with special features, such as :

FEATURES	BENEFITS
Excellent antiwear and anticorrosion properties	Perfectly protects hydraulic system parts
High viscosity index and high pour point	Guarantees a perfect functioning of central hydraulics even at low temperatures

### SPECIFICATIONS

KENNOL LDS FLUID has been developed to meet the highest international standards, including :

<b>PSA</b>	<b>S 71 2710</b>
<b>ISO</b>	<b>7308</b>
Color	Orange
Viscosity @ 40°C (cSt)	18,4
Viscosity @ 100°C (cSt)	6,3
Viscosity Index	340
Density @ 15,6°C	0,829
Viscosity @ -40°C (cSt)	940
Closed Flash Point, °C	135
Acid Number (mgKOH/g)	0,2

KENNOL LDS FLUID has been developed to answer the needs of specific hydraulic systems and particular absorbing applications for an improved ride quality. Because this product was born on the track.

Direct download here : [http://www.kennol.com/FT/KENNOL\\_LDS\\_FLUID\\_EN.pdf](http://www.kennol.com/FT/KENNOL_LDS_FLUID_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2019 KENNOL. All rights reserved.