

TOURING C4 5W30

PRODUCT DESCRIPTION

KENNOL TOURING C4 5W30 is a top level fully synthetic motor oil with reduced sulfated ashes, phosphorus and sulphur content (Low SAPS).

Recommended for recent RENAULT passenger cars and equipped with exhaust treatment systems such as DPF (Diesel Particulate Filters), TWC (Three Way Catalyst).

PROPERTIES

KENNOL TOURING C4 5W30 is formulated from synthetic bases combined with latest performance additives to provide with special features, such as :

FEATURES	BENEFITS
High fluidity	Allows fuel saving and helps to protect environment
Very high detergent and dispersant properties	Ensures excellent engine protection and cleanness and reduces exhaust fumes
Very high thermal stability	Guarantees excellent protection at high temperature
Low volatility	Enables low oil consumption

SPECIFICATIONS

KENNOL TOURING C4 5W30 has been developed to meet the highest international standards, including :

SAE	5W30
ACEA	C4
RENAULT	RN 0720
Viscosity @ 40°C (cSt)	70
Viscosity @ 100°C (cSt)	11,8
Viscosity Index	175
Viscosity CCS (cP)	6000 (@ -30°C)
Density @ 20°C	0,851
Viscosity HTHS (at 150 °C under high shear 106 s-1) (cP)	3,6
Pour Point, °C	-37
Flash Point, °C	> 210
Volatility Noack 1H @ 250°C (%w)	11
TBN (mg KOH/g)	6

KENNOL TOURING C4 5W30 has been mainly developed to answer the needs of modern engines. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_TOURING_C4_5W30_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.