

EASYGEAR 75W80

PRODUCT DESCRIPTION

KENNOL EASYGEAR 75W80 is a semi-synthetic high performance extreme pressure oil, especially developed for mechanical gearboxes and axles of passenger cars.

PROPERTIES

KENNOL EASYGEAR 75W80 is formulated from high quality bases and additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear and extreme pressure properties	Material life extended
High thermal and gear stability	Optimal performance over time
Low viscosity at low temperature	Easier gear shift when cold

SPECIFICATIONS

KENNOL CHF FLUID has been developed to meet the highest international standards, including :

SAE	75W80
API	GL5
MILL.	2105D
Viscosity @ 40°C, cSt	49,5
Viscosity @ 100°C, cSt	7,5
Viscosity Index	113
Density @ 20°C	0,876
Pour Point [°C]	< -40
Flash Point [°C]	> 210

KENNOL EASYGEAR 75W80 has been mainly developed to answer the needs of precise applications, including fast gear shifting, and demanding situations pushing the axles more than usual. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/EASYGEAR_75W80.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2010 KENNOL. All rights reserved.