

ECOLOGY C3 5W30

PRODUCT DESCRIPTION

KENNOL ECOLOGY C3 5W30 is a top level fully synthetic motor oil with reduced sulfated ashes, phosphorus and sulphur content (Mid SAPS).

Recommended for recent BMW, MERCEDES, OPEL, CHRYSLER, MITSUBISHI, KIA, HYUNDAI, SUZUKI,... passenger cars, equipped with exhaust treatment systems such as DPF (Diesel Particulate Filters), TWC (Three Way Catalyst).

PROPERTIES

KENNOL ECOLOGY C3 5W30 is formulated from synthetic bases combined with latest performance additives to provide with special features, such as :

FEATURES	BENEFITS
High fluidity	Allows fuel saving and helps to protect environment
Very high detergent and dispersant properties	Ensures excellent engine protection and cleanness and reduces exhaust fumes
Very high thermal stability	Guarantees good protection at high temperature
Low volatility	Enables low oil consumption

SPECIFICATIONS

KENNOL ECOLOGY C3 5W30 has been developed to meet the highest international standards, including :

SAE	5W30
ACEA	A3/B4/C3
API	SM/CF
MB	229.51
BMW	LL-04
VW	502.00/505.00/505.01
Viscosity @ 40°C (cSt)	70
Viscosity @ 100°C (cSt)	11,5
Viscosity Index	165
Viscosity CCS (cP)	6000 (at -30°C)
Density @ 20°C	0,85
Viscosity HTHS (at 150 °C under high shear 106 s-1) (cP)	> 3,5
Pour Point, °C	< -35
Flash Point, °C	>210
TBN (mg KOH/g)	7

KENNOL ECOLOGY C3 5W30 has been mainly developed to answer the specific needs of modern engines. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/ECOLOGY_C3_5W30.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2010 KENNOL. All rights reserved.