

AUTOSHIFT MB 236.14

PRODUCT DESCRIPTION

KENNOL AUTOSHIFT MB 236.14 is a high performance 100% synthetic lubricant, for vehicle automatic transmissions requiring a low viscosity fluid. It is especially suitable for Mercedes automatic transmissions requiring the MB 236.14 standard (models: AMG, RWD 7-speed (NAG2) and 5-speed transmissions fitted with a viscous coupling locking system)

PROPERTIES

KENNOL AUTOSHIFT MB 236.14 is formulated from synthetic bases and top level performance additives to provide with special features, such as :

FEATURES	BENEFITS
Exceptional thermal and shearing stability	Optimal performance over time Extends the life of the system and improves its performances in severe usage conditions
Low viscosity	Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag

SPECIFICATIONS

KENNOL AUTOSHIFT MB 236.14 has been developed to meet the highest international standards, including :

MB	236.12 / 236.14 / 236.15 / 236.41
GM	Dexron VI / AW1 88863400 / 88863401
MERCON	LV
VW	G 052 533 / G 055 005 / G 055 540 G 055 162 / G 060 162
JASO	M315, Class 1A
TOYOTA	Type WS
AISIN WARNER	JWS 3324
NISSAN	Matic S
HONDA	ATF-DW1
HYUNDAI	SP-IV / SPH-IV NWS-9638 T-5 / 040000C90SG
SHELL	M-1375.4 (ZF Lifeguardfluid 6) M-L 12108 (ZF Lifeguardfluid 8)
ATF	SHELL 3353 / 134 / M-1375.4
BENTLEY	PY112995PA
BMW	83 22 0 142 516 / 83 22 2 152 426 83 22 0 397 114 / 163 514
FORD	XT-6-QSP
JAGUAR	Fluid 8432
LAND ROVER	TYK500050 / LR0022460
MASERATI	231603
MAZDA	FZ
MITSUBISHI	ATF-J3
PORSCHE	000 043 304 00
SAAB	93 165 147 - AW - 1
Viscosity @ 40°C, cSt	30
Viscosity @ 100°C, cSt	6,1
Viscosity Index	155
Density @ 20°C	0,843
Pour Point, °C	<-35
Flash Point, °C	>190

KENNOL AUTOSHIFT MB 236.14 has been mainly developed to answer the needs of demanding applications, such as racing and performance vehicles, as well as every situation pushing the gearboxes and torque converters more than usual.

Direct download here : http://www.kennol.com/FT/KENNOL_AUTOSHIFT_MB_236_14_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.