

BRAKE FLUID

DOT 5.1

PRODUCT DESCRIPTION

KENNOL BRAKE FLUID is a fully synthetic high performance brake fluid, especially developed for vehicles whom manufacturer requires a synthetic fluid. Thanks to its low viscosity at cold temperature, KENNOL BRAKE FLUID is suitable for vehicles with ABS or ASC braking systems (antiskidding).

BE CAREFUL :

- Do not use where a mineral fluid (LHM) is required
- Do not blend with silicon based fluids
- Avoid contact with paintworks
- Keep in a dry place

PROPERTIES

KENNOL BRAKE FLUID is formulated from high quality bases and additives to provide with special features, such as :

FEATURES	BENEFITS
Low moisture absorption and high boiling point properties	Vapor-lock issues avoided

SPECIFICATIONS

KENNOL BRAKE FLUID has been developed to exceed the highest international standards, including :

SAE	J1703
FMVSS	116
DOT	3, 4, 5.1
Viscosity @ -40°C (mm ² /s)	<900
pH	8
Water (%)	<0,1
Dry Boiling Point (°C)	>260
Wet Boiling Point (°C)	>180

KENNOL BRAKE FLUID has been developed to answer the needs of control in extreme situations as well as every situation requiring more brake efficiency than usual. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_BRAKE_FLUID_DOT_5.1_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2013 KENNOL. All rights reserved.