

CVT FLUID

PRODUCT DESCRIPTION

KENNOL CVT FLUID is a fully synthetic lubricant, especially developed for most automatic gearboxes with Continuously Variable Transmissions (CVT) both belts and chains. It is neither suitable for hybrid vehicles CVT, nor for Direct-Shift Gearboxes or automatic Dual Clutch Transmissions (DSG or DCT).

Before use and if in doubt, refer to the vehicle service manual.

PROPERTIES

KENNOL CVT FLUID is formulated from synthetic bases and top level performance additives to provide with special features, such as :

FEATURES	BENEFITS
Exceptional thermal and shearing stability	Optimal performance over time Extends the life of the system and improves its performances in severe usage conditions
Low viscosity	Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag

SPECIFICATIONS

KENNOL CVT FLUID has been developed to meet the highest international standards, including :

Audi (TL 52180, TL 52516, G 052 180, G 052 516)	Mercedes Benz (CVT28, MB 236.20)
BMW (83 22 0 136 376, 83 22 0 429 154, EZL799, EZL 799A)	Mini Cooper (EZL 799, EZL 799A, ZF CVT V1)
Daihatsu (Ammix CVTF-DC, Ammix CVTF-DFE)	Mitsubishi (DiaQueen CVTF-J1, DiaQueen CVTF-J4, SP-III)
Dodge (NS-2, CVTF+4, Mopar CVT+4)	Nissan (NS-1, NS-2, NS-3)
Ford (CVT23, WSS-M2C928-A, CVT30, WSS-M2C933-A, Motorcraft XT-7-QCFT, MERCON C)	Punch (EZL 799 / EZL 799A)
General Motors (DEX-CVT, GM-CVT)	Renault (Elfmatic CVT)
Honda (HMMF, HCF-2)	Saturn (DEX-CVT)
Hyundai (SP-CVT 1, SP-III)	Subaru (e-CVTF, i-CVTF, Lineartronic CVTF II, CV-30, NS-2)
Jeep (NS-2, CVTF+4, Mopar CVT+4)	Suzuki (CVTF 3320, TC, NS-2, CVTF Green 1, Shell green 1V, CVTF Fluid Green 2)
Kia (SP-CVT 1, SP-III)	Toyota (TC, FE)
Lexus (TC)	VW (TL 52180, TL 52516, G 052 180, G 052 516)
Mazda (CVTF 3320)	

Viscosity @ 40°C, cSt	33,7
Viscosity @ 100°C, cSt	7,2
Viscosity Index	185
Density @ 20°C	0,851
Pour Point, °C	<-35
Flash Point, °C	>180

KENNOL CVT FLUID has been mainly developed to answer the needs of demanding applications, such as racing and performance vehicles, as well as every situation pushing the gearboxes and torque converters more than usual.

Because this product was born on the track.

Téléchargement direct : http://www.kennol.com/FT/KENNOL_CVT_FLUID_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2017 KENNOL. All rights reserved.