

GREASING LITHIUM

PRODUCT DESCRIPTION

KENNOL GREASING LITHIUM is a high quality grease for multiple use, particularly for the car, industry, and civil engineering.

PROPERTIES

KENNOL GREASING LITHIUM bears the following features:

| FEATURES | BENEFITS |
|-------------------------------|--|
| «Extreme pressure» properties | Wear components in movement reduced. |
| Very good sticking | Excellent quality in service. |
| Very good lubricating power | Protection against micro-welding and metal wrenches. |

SPECIFICATIONS

KENNOL GREASING LITHIUM has been developed to exceed the highest international standards, including:

| | NLGI 2 |
|--|-------------|
| Nature of soap | Lithium |
| Colour | Amber |
| Appearance | Smooth |
| Penetration [NF T 60-132] (1/10 mm) | 265/285 |
| Water solubility | Insoluble |
| Limit temperature of use (°C) | -20 to +140 |
| 4 weld balls [ASTM D 2596] (kg) | 200 |
| 4 wear balls 1 h/40 kg [ASTM D 2266] (mm) | 0,7 |
| Corrosion Cu 3 h/100°C [ASTM D 4048] (b) | 1 |
| Oxidation after 100 h [ASTM D 942] (psi) | Inf. to 7 |
| EMCOR Test distilled water [NF T 60-135] | 1 |
| Wash out [ASTM D 1264] à 80°C % poids | Inf. to 4 |
| Wheel bearing [ASTM D 1263] à 105°C | 1 |
| Penetrating testing 30 h/100°C [AIR 1650 A] % weight | Inf. to 3 |

Direct download here: http://www.kennol.com/FT/KENNOL_GREASING_LITHIUM_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2014 KENNOL. All rights reserved.