

## POWER FLUID DEXRON

### PRODUCT DESCRIPTION

KENNOL POWER FLUID DEXRON is a mineral oil developed for power steering systems of vehicles for which a DEXRON II D fluid is recommended by manufacturer.

KENNOL POWER FLUID DEXRON can be used in automatic gearboxes.

### PROPERTIES

KENNOL POWER FLUID DEXRON is formulated from quality bases and additives to provide with special features, such as :

FEATURES	BENEFITS
Very good thermal and shearing stability	Extends the life of the system and improves its performance in severe usage conditions
Good air-release properties	Limits the cavitation problems

### SPECIFICATIONS

KENNOL POWER FLUID DEXRON has been developed to meet the highest international standards, including :

GM	Dexron IID
Viscosity @ 40°C (cSt)	38
Viscosity @ 100°C (cSt)	7,4
Viscosity Index	165
Density @ 20°C	0,869
Pour Point (°C)	< -35
Flash Point, °C	> 190

KENNOL POWER FLUID DEXRON has been mainly developed to answer the specific needs of DEXRON II D level power steering systems. Because this product was born on the track.

Direct download here: [http://www.kennol.com/FT/KENNOL\\_POWER\\_FLUID\\_DEXRON\\_EN.pdf](http://www.kennol.com/FT/KENNOL_POWER_FLUID_DEXRON_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2013 KENNOL. All rights reserved.