

## TOURING 15W40

### PRODUCT DESCRIPTION

KENNOL TOURING 15W40 is a high quality mineral motor oil, adapted for petrol or diesel passenger cars, equipped or not with turbo. Its wide viscosity range and its high viscosity index allow a use all year round, in urban area as well as for long motorway driving.

This motor oil can also be used in trucks.

### PROPERTIES

KENNOL TOURING 15W40 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

| FEATURES                          | BENEFITS                                  |
|-----------------------------------|---|
| Antiwear and detergent properties | Extends engine life                       |
| High viscosity                    | Very good protection at high temperatures |
| Low volatility                    | Guarantees low oil consumption            |
| High lubricating power            | Enables high operational safety           |

### SPECIFICATIONS

KENNOL TOURING 15W40 has been developed to meet the highest international standards, including :

|  |                |
|--|----------------|
| SAE  | 15W40          |
| ACEA   | A3/B4          |
| API  | SL/CF/CH-4     |
| MB   | 228.3          |
| MAN  | 3275           |
| VOLVO  | VDS-2          |
| RENAULT  | RD-2           |
| MACK   | EO-M+          |
| CUMMINS  | CES 20077      |
| CAT  | ECF-1A         |
| DQC  | II             |
| MTU  | 2.0            |
| Viscosity @ 40°C (cSt)   | 109            |
| Viscosity @ 100°C (cSt)  | 14,6           |
| Viscosity Index  | 137            |
| Viscosity CCS (cP)   | 6500 (à -20°C) |
| Density @ 20°C   | 0,88           |
| Viscosity HTHS (at 150 °C under high shear 10 <sup>6</sup> s-1) (cP) | > 3.5          |
| Pour Point (°C)  | < -25          |
| Flash Point, °C  | > 210          |
| TBN (mg KOH/g)   | 10,4           |

KENNOL TOURING 15W40 has been mainly developed to answer the needs of drivers asking for an alternative solution with their petrol or diesel engine. Because this product was born on the track.

Direct download here : [http://www.kennol.com/FT/KENNOL\\_TOURING\\_15W40\\_EN.pdf](http://www.kennol.com/FT/KENNOL_TOURING_15W40_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2018 KENNOL. All rights reserved.