

## TOURING 15W40

### PRODUCT DESCRIPTION

KENNOL TOURING 15W40 is a high quality mineral motor oil, adapted for petrol or diesel passenger cars, equipped or not with turbo. Its wide viscosity range and its high viscosity index allow a use all year round, in urban area as well as for long motorway driving.

This motor oil can also be used in trucks.

### PROPERTIES

KENNOL TOURING 15W40 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
High viscosity	Very good protection at high temperatures
Low volatility	Guarantees low oil consumption
High lubricating power	Enables high operational safety

### SPECIFICATIONS

KENNOL TOURING 15W40 has been developed to meet the highest international standards, including :

<b>SAE</b>	<b>15W40</b>
<b>ACEA</b>	<b>A3/B3</b>
<b>API</b>	<b>SL/CF/CG4</b>
<b>MB</b>	<b>229.1</b>
<b>VW</b>	<b>501.01/505.00</b>
Viscosity @ 40°C (cSt)	109
Viscosity @ 100°C (cSt)	14,6
Viscosity Index	137
Viscosity CCS (cP)	6500 (à -20°C)
Density @ 20°C	0,88
Viscosity HTHS (at 150 °C under high shear 10 <sup>6</sup> s-1) (cP)	> 3.5
Pour Point (°C)	< -25
Flash Point, °C	> 210
TBN (mg KOH/g)	10,4

KENNOL TOURING 15W40 has been mainly developed to answer the needs of drivers asking for an alternative solution with their petrol or diesel engine. Because this product was born on the track.

Direct download here : [http://www.kennol.com/FT/KENNOL\\_TOURING\\_15W40\\_EN.pdf](http://www.kennol.com/FT/KENNOL_TOURING_15W40_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2017 KENNOL. All rights reserved.