



ASKING
FOR
ASPHALT

TRUCKING MT 4 10W40

PRODUCT DESCRIPTION

KENNOL TRUCKING MT 4 10W40 is a semi-synthetic 4 stroke high performance oil for heavy truck diesel engines, agricultural equipment and civil engineering, with or without turbo, used in extreme conditions.

Recommended for EURO 3, 4, 5 without particulate filters.

PROPERTIES

KENNOL TRUCKING MT 4 10W40 is formulated from bases combined with additives to provide with features, such as :

FEATURES	BENEFITS
Detergent and dispersant properties	Engine better cleaned. Extended drain intervals for heavy trucks (up to 60000 kms according to the service).
Low viscosity at cold temperature	Limit wear at start.

SPECIFICATIONS

KENNOL TRUCKING MT 4 10W40 has been developed to meet the highest international standards, including:

SAE	10W40
API	CI4
ACEA	E7 / B4
MAN	M3275-1
VOLVO	VDS 3
RENAULT TRUCKS	RLD 2
JASO	DH-1
GLOBAL	DHD-1
MERCEDES	MB 228.3 / 229.1
CUMMINS	CES 20076/77/78
MACK	EO-N
MTU DDC	Type 2
DETROIT DIESEL	DDC 93K215
DEUTZ	DQC III-10
VOITH / MB	Voith A / MB 235.27
Viscosity @ 40°C (cSt)	100
Viscosity @ 100°C (cSt)	14
Viscosity index	150
Density	0,872
Dynamic viscosity @ -25°C (cP)	6500

Direct download here: http://www.kennol.com/FR/FT/KENNOL_TRUCKING_MT4_10W40_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.