

## PRODUCT DESCRIPTION

KENNOL ULTIMA 10W60 is a 100% top-of-the-range lubricant specially designed to provide exceptional levels of performance and protection to engines subjected to extreme operating conditions.

It is formulated from Polyalphaolefins (PAO), Esters and additives carefully selected.

## PROPERTIES

KENNOL ULTIMA 10W60 is formulated from high quality synthetic bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life and prevents formation of black sludge
Low viscosity at low temperatures	Excellent oil flow into the engines even at cold start
Excellent thermal stability	Guarantees full protection at high temperature
High lubricating power	Enables maximum performance at high speed

## SPECIFICATIONS

KENNOL ULTIMA 10W60 has been developed to meet the highest international standards, including :

<b>SAE</b>	<b>10W60</b>
<b>API</b>	<b>SN/CF</b>
<b>ACEA</b>	<b>A3/B4</b>
<b>MB</b>	<b>229.3</b>
<b>VW</b>	<b>502.00 / 505.00</b>
Viscosity @ 40°C, cSt	164
Viscosity @ 100°C, cSt	23,1
Viscosity Index	170
Viscosity CCS @ -25°C, cP	6800
Density @ 20°C	0,86
Viscosity HTHS (at 150 °C under high shear 106 s-1) (cP)	> 3.5
Pour Point, °C	< -31
Flash Point, °C	> 210
TBN, mg KOH/g	9.4

KENNOL ULTIMA 10W60 has been mainly developed to answer the needs of demanding applications, such as race environment and endurance requirements. Because this product was born on the track.

Direct download here : [http://www.kennol.com/FT/KENNOL\\_ULTIMA\\_10W60\\_EN.pdf](http://www.kennol.com/FT/KENNOL_ULTIMA_10W60_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2017 KENNOL. All rights reserved.