

UTTOFARM

PRODUCT DESCRIPTION

KENNOL UTTOFARM is a high performance multi purpose lubricant developed for the lubrication of all major tractor components except engines : gearboxes, wet brakes, transmission and hydraulic systems.

PROPERTIES

KENNOL UTTOFARM is formulated from bases and additives to provide with features, such as:

FEATURES	BENEFITS
Very high viscosity index	Easy start up at low tempeture High safety potential at high temperature.
Antifoaming properties	Cavitation problem in hydraulic pumps prevented.
«Extreme pressure» additive	Protection against micro-welds and metal wrenching.
Friction modifying additive	Constant brake of wet brakes and clutches without noise or jerks ensured.

SPECIFICATIONS

KENNOL UTTOFARM has been developed to exceed the highest international standards, including:

	ISO VG 68
SAE	10W30
API	GL4
JI CASE	MS 1206 - MS 1207
JOHN DEERE	JDM J20C/D
FORD NEW HOLLAND	M2C 134 A/B/C/D, M2C 86 B/C, FNHA 2C 201.00
MASSEY FERGUSON	M1135 / M1143 / M1145
ZF TE-ML	03F/05F
CNH MAT	3525
VOLVO	VCE-WB 101
CATERPILLAR	T02
ALLISON	C3/C4
Density at 20°C	0,885
Viscosity at 40°C (cSt)	62
Viscosity at 100°C (cSt)	10
Viscosity index	150
Dynamic viscosity at -25°C (cP)	6800

Direct download here: http://www.kennol.com/FT/KENNOL_UTTOFARM_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2014 KENNOL. All rights reserved.