

SPRINT 15W50 4T

PRODUCT DESCRIPTION

KENNOL SPRINT 15W50 4T is a high quality mineral oil for 4-stroke engines of scooters and motorcycles, especially for large V engines delivering power and torque at low RPMs. This oil is miscible with any classic motor oil.

Thanks to specific additives, KENNOL SPRINT 15W50 4T is also perfectly suitable for integrated gearboxes lubrication.

PROPERTIES

KENNOL SPRINT 15W50 4T is formulated from high quality bases and performance additives with special features, such as :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
Extreme pressure additives	Good lubrication of integrated gearboxes
High viscosity at high temperature	Excellent protection with very high temperatures
Low volatility	Guarantees low oil consumption
High lubricating power	Enables high operational safety

SPECIFICATIONS

KENNOL SPRINT 15W50 4T has been developed to meet the highest international standards, including :

SAE	15W50
JASO	MA
API	SJ
Viscosity @ 40°C (cSt)	135
Viscosity @ 100°C (cSt)	17,5
Viscosity Index	145
Viscosity CCS (cP)	6200 (at -20°C)
Density @ 20°C	0,882
Pour Point (°C)	< -25
Flash Point, °C	>210

KENNOL SPRINT 15W50 4T has been mainly developed to give 4-stroke engines of scooters and motorcycles a global solution for engine and integrated gearbox lubrication. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/SPRINT_15W50_4T.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2010 KENNOL. All rights reserved.